

jc685 U.S. PTO



02/25/00

LAW OFFICES

SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC

2100 PENNSYLVANIA AVENUE, N W

WASHINGTON, DC 20037-3213

TELEPHONE (202) 293-7060

FACSIMILE (202) 293-7860

JAPAN OFFICE

TOEI NISHI SHIMBASHI BLDG 4F

13-5 NISHI SHIMBASHI 1-CHOME

MINATO-KU, TOKYO 105, JAPAN

TELEPHONE (03) 3503-3760

FACSIMILE (03) 3503-3756

CALIFORNIA OFFICE

1010 EL CAMINO REAL

MENLO PARK, CA 94025

TELEPHONE (650) 325-5800

FACSIMILE (650) 325-6606

February 25, 2000

Ass't Commissioner of Patents
Washington, D.C. 20231

ATT: APPLICATION BRANCH

Re: U.S. Application of Alfredo DAL PAN for "CONTAINER-FILLING DEVICE FOR LOST-FOAM CASTING SYSTEMS"

Our Ref: Q-57966

Sir:

Attached hereto is the application identified above including the executed Declaration, Assignment, priority document, Information Disclosure Statement and 3 sheets of formal drawings containing Figures 1-3. The government filing fee is calculated as follows:

Total claims	16 - 20 = 00	x \$18(09) =	
Independent Claims	01 - 03 = 00	x \$78(39) =	
Base Fee (\$690.00/\$345.00)			690.00
Assignment Recordal Fee (\$40.00)			40.00
Multiple Dependent Claim Fee (\$260./\$130.)			
Foreign Language Filing Fee (\$130.00)			

TOTAL FILING FEE 730.00

A check for the initial filing fee of the application in the amount of \$690. is attached along with a second check in the amount of \$40.00 for recordation of the Assignment. The Patent Office is also authorized to charge and required fee or credit any overpayment to Deposit Account No. 19-4880. The Commissioner is hereby authorized to charge any fees under 37 C.F.R. §§ 1.16 and 1.17 which may be required during the entire pendency of the application to Deposit Account No. 19-4880.

Priority is claimed for this application from European Application No. 99830106.3 filed February 26, 1999.

Respectfully submitted,

Robert V. Sloan

Reg. No. 22,775

RVS:jljg

Attachments:



UNITED STATES OF AMERICA

TO WHOM IT MAY CONCERN:

BE IT KNOWN THAT Alfredo DAL PAN
of Via Induno 16, I-10137 TORINO (Italy)

has invented certain new and useful improvements in and relating to: "Container-filling
device for lost-foam casting systems" of which the following is a specification

005000 91221500

DESCRIPTION

The present invention relates to devices for filling containers in lost-foam casting systems.

Lost-foam casting technique represents an ever more widely employed foundry technique that is essentially based on the preparation of a model, generally made of polystyrene or some similar material, that exactly reproduces the characteristics of the piece to be cast. This model is inserted in a container (flask) filled with sand, which is then vibrated until the sand is distributed and compacted in such a manner as to adapt itself closely to and reproduce the exact shape of the model. Hot casting material (typically molten metal) is then poured into the space occupied by the model. The casting material dissolves the model and thus goes to occupy the space that was previously occupied by the model in the surrounding sand. The final result is therefore the obtainment of a casting, i.e. a workpiece, that exactly reproduces the shape of the model.

The present invention comes to grips, first and foremost, with the problem of optimizing the operations that lead to the model being inserted or «drowned» in the sand prior to its compaction by vibration. This, in particular, as regards the need of avoiding such phenomena as breakage or displacement of the model (typically realized in the form of a cluster of smaller individual models). Subordinately, the invention also sets out to realize a filling device of the intelligent type, capable - in particular - of identifying the individual model and/or the container into which it has been inserted and thus to render possible, for example, selective specialization of the various processing

operations, this to the point of arriving at treating each model/casting in accordance with a particular tailor-made processing «recipe».

According to the present invention, this scope is attained by means of a container-filling device for lost-foam casting systems, including in a single operational combination:

- supporting means for containers with associated vibration means to set the said containers into vibration;
- sand-feeding means capable of selectively feeding dosed quantities of sand into the said containers; and
- positioning means that can selectively be associated with the said containers to position foam models into the said containers; the said positioning means being capable of sustaining the said models both while the sand is being fed into the containers by the said feeding means and while the containers containing the said models are being vibrated by the said vibration means.

The invention will now be described, though purely by way of example and not to be considered limitative in any way, by reference to the attached drawings, where:

Figure 1 shows a general view in side elevation of a container-filling station in a lost-foam casting system;

Figure 2 shows a larger-scale view of the part of Figure 1 indicated by the arrow II;

Figure 3 shows another view in side elevation of the device shown in Figure 2, but this time seen in a direction that is substantially orthogonal with respect to the viewing direction of Figure 2.

The general view of Figure 1 represents a station 2 for filling the containers of a lost-foam casting plant or system. The plant in question could consist, for example, of the system described in greater detail in a European patent application filed on the same date by the same applicants.

At the station 2 the models S are inserted into the containers C in which the casting operations are to be performed, the said containers being subsequently filled with sand and subjected to vibration, so that the sand will eventually become compacted and be in close contact with the outer surface of the said models S.

The movement of the containers C is realized (from left to right, with respect to the viewing direction of Figure 1) in such a way as to produce a step-by-step forward motion of the containers below a main silo 20 designed for feeding sand by means of free fall to four successive filling substations. The said filling substations are consecutively numbered from 21 to 24 in the direction in which the containers C move forward beneath the silo 20. For this purpose the containers C are usually placed on platform trolleys (carriers) 50 that move forward (under the action of movement control means not shown on the drawing) on rotating bodies 51 that could be, for example, rollers or wheels.

In particular, the substation 21 can be defined as a prefilling station: here a certain quantity of sand F originating from within the silo 20 is fed through a duct 25 and an associated hopper 26 into the bottom part of the container C that at any given moment happens to be in the substation 21.

The next substation, indicated by 22, has a somewhat more complex structure that will be described in greater detail further on. At the substation 22 the polystyrene models or outlines S (usually in the form of model clusters, as already noted) are arranged inside the containers that have already had a certain quantity of sand filled into their bottom parts at the substation 21. The models S are usually taken from a feeder turntable (not shown in the figure) by means of a robot of which only the pick-up arm is shown by means of a dotted line in Figure 2, where it is identified by the letter R. The design and operating details of the robot in question (which could be of any known type, an anthropomorphic robot being a case in point) are not in themselves relevant for a proper understanding of the invention and will not therefore be described in any detail. Here it will be sufficient to recall the fact that the model S normally consists of a model cluster provided with a grip formation T by means of which it can be picked up by the arm R of the robot to be sustained centrally, i.e. in a position that substantially coincides with the barycentre, by a positioning element indicated by the reference number 27 and subsequently to be described in greater detail.

At the substation 22 the container C receives, this time from the hopper 30, a further quantity of sand intended to cover the model S for a substantial part of its height.

At the said substation 22 the container C is also lifted slightly in a vertical direction to detach it from the conveyor structure 50, while the lifting organs 31a (see Figure 3) that perform the said lifting action are caused to vibrate by means of a vibration device 32a. In this way the sand inside the container C is subjected to the necessary

vibration and compaction action. Both the pick-up (gripping) organs 31a and the vibration device 32a are well known to the state of the art and need not therefore here be described in further detail.

The action of filling the container C with sand is completed at the subsequent substations indicated by 23 and 24. As far as complexity is concerned, these two substations may be said to be intermediate between the complexity of substation 21 and that of substation 22. In fact, the substations 23 and 24 include respective ducts 33 and 34 for feeding sand from the silo 20 into the hoppers 35 and 36. In this case, of course, there is no longer present the complex of parts and elements needed for arranging the models S inside the containers C. But what does have to be present at this stage are the lifting organs and the vibration devices 32b and 32c, which are substantially similar to the devices 31a and 32a that have already been mentioned in connection with substation 22.

The choice of realizing the filling and the vibration of the containers C in successive phases is in keeping with the need for gradual immersion of the model S in the sand, thereby assuring that the sand around it will become fully compacted. This choice is also imposed by the general needs bound up with the timing of the forward movement of the containers C on the conveyor system and assuring the desired productivity levels.

With the help of Figure 3, we can now pass on to describing in greater detail the structure of the device that constitutes the substation 22. Referring to the side elevation show in this figure, one notes the presence of an

upright 100 in position that can be described as generically by the side of the line along which the trolleys 50 bearing the containers C are moving forward.

Mounted on the said upright 100 in such a way as to enable it to move up and down under the action of an appropriate fluid jack 101 there is a mobile item of equipment 102 having the general structure of a projecting bracket. This bracket-like structure 102 sustains the hopper 30 below the bottom outlet opening 20a of the silo 20 and also extends downwards in the form of a cage structure 29 which sustains a frame 103 in a position that may be described as generically below the hopper 30. In its turn, the said frame 103 sustains the previously mentioned positioning element 27 in a generically central position.

The complex of parts just described, usually realized in the form of structural steelwork, is therefore capable of moving vertically along an axis X_c along which the following elements are arranged:

- the bottom outlet opening 20a of the silo 20,
- the hopper 30 with its discharge opening 104, complete with an appropriate opening and closing system 105 of a known type,
- the frame 103 with the positioning element 27 that, in its turn, sustains the model S in a central position, and
- the container C that at that particular moment occupies the substation 22.

The bracket-like structure 102 is preferably realized in the form of a square metal frame capable of carrying the hopper 30 through the intermediary of appropriate load

cells 106 (which may be three in number, for example) on which there rest the correspondingly positioned bracket structures 107 projecting radially from the upper edge of the hopper 30. The load cells 106 therefore provide signals that indicate the quantity of sand present in the hopper 30 and, consequently, the quantity of sand that will eventually be transferred into the container C below the hopper.

The frame 103 is suspended from the structure 102 by means of the legs 108, which do not in any way encumber the space within the frame 103 intended to be occupied by the positioning element 27.

The said element includes a central hub 109 that carries a clamp 110 with a control unit 116. The hub 109 is sustained by a series of spokes 111 that connect it to an inner frame on which there is mounted at least one other clamp 112 with its own control unit 113. Preferably, however, there will be three such clamps, distributed in a substantially uniform manner along the circumference of the inner frame.

The frame 103 also carries, usually mounted on the said inner frame one or more centering formations 114.

The said centering formations preferably include a fork element 114a, which - when the element 27 comes to be located (as will be described in greater detail further on) at the level of the upper rim of the container C - will engage with an appropriate counterpart projecting from that rim and will thus avoid undesired relative rotations. Usually there will also be present a pin 114b, as well as a corresponding cavity

115 carried in a generically peripheral position by the inner frame of the frame 103.

The operating units 116 and 113 of the clamps 110 and 112 are in their turn controlled, just like the unit that controls the aperture of the outlet opening 20a of the silo 20, by the unit 105 controlling the feeding of the sand from the bottom opening 104 of the hopper 30, the load cells 106 and the control unit of the jack 101, by a processor-type control unit K that may consist, for example, of a so-called PLC (acronym of Programmable Logic Controller) or some equivalent processing unit that controls (in accordance with criteria that are in themselves known and/or will be rendered obvious by the present description) the operation of these organs in a manner that is fully coordinated with the operation of the other parts of the plant, especially the robot R and the trolleys 50.

The operating unit 113 is preferably configured in such a manner that - with the system at rest - the return elements, springs for example, will keep the clamps 112 in their fully open position.

As can be more readily appreciated from the view reproduced in Figure 2, the element 27 is not fixed to the frame 103, but rather rests freely - and, be it noted, in an exactly centred position - on the said frame, and can therefore become disengaged from the frame 103 by performing an upward movement relative to it.

The operating cycle of the device constituting the substation 22 can be summarily described in the following terms.

The device gets ready to receive a container C (already containing the quantity it received at the substation 21 on the upstream side) while the complex of parts sustained by the structure 102 is in the position shown by means of full lines in both Figure 2 and Figure 3. In other words, when the substation is ready to receive a new container, the fluid jack 101 keeps the entire structure at the upper end of its travel.

Let us suppose that when the container C arrives, as also in the phase that immediately precedes or follows its arrival, the robot R has already picked up a model S and inserted the grip formation T with which it is provided into the clamps 110. The clamp is first maintained in its open position, which enables it to receive the said grip formation T, and is then closed around it, so that it will come to carry the model S. After releasing the model S it has just loaded into the device 22, the robot arm R returns towards the structure from which the models are picked up (which is typically of the turntable type and is not illustrated) in search of a new model S.

In the meantime, the outlet aperture 20a of the silo 20 has been opened, so that there has dropped into the hopper 30 a quantity of sand corresponding to the quantity it is subsequently desired to discharge into the container C.

At this point the jack 101 is operated in such a way as to cause the entire supporting structure 102 to become gradually lowered towards the container C. This operation ensures that the model S will be lowered into the container C.

In the course of this operation the model is lowered from the

position shown in Figures 2 and 3 by means of full broken lines to the position indicated by means of the chain-dotted lines in the same figures.

In the lowered position previously referred to, the model S usually comes to rest on top of the sand F already contained in the container C as a result of the pre-filling operation previously carried out at the substation 21. In any case, the said downward movement causes the clamps 112 to engage the upper rim of the container C. Activation of the unit 113 (likewise controlled by the PLC K) ensures that the clamps 112, originally open, will now tighten and grip the rim of the container C: the series of spokes 111, and therefore also the hub 109 they carry in a central position, will thus come to constitute what is *de facto* a single piece with the container C. This applies also as regards the clamps 110 carried by the hub 109 and, consequently, the model S.

In the said lowered position, therefore, the operating unit 105 controlling the bottom outlet of the hopper 30 can be activated to open the said outlet, so that the quantity of sand contained in it will now be discharged into the container C and there cover the model S.

It will readily be appreciated that the said model is kept firmly in a fixed position with respect to the container C by means of the clamp 110 carried by the hub 109, which in its turn is linked by means of the spokes 111 to the clamps 112 that grip the rim of the container C.

The descending sand will not therefore be able to cause any undesired displacements of the model S while the container is being filled. This even when the sand comes down in a rush of

considerable intensity and/or when the model has surfaces orientated in such a manner as to exert a certain deflection action on the falling sand S (so that the model, by reaction, becomes subject to a certain fluid dynamic thrust).

Examination of Figure 2 also makes it clear that, since the clamps 112 grip the rim of the container C, the positioning element 27, taken as a whole, will no longer be able to follow the downward movement of the frame 103. The travel of the jack 101 is in fact regulated (in a manner coordinated with all the other dimensional magnitudes in play) in such a manner as to ensure that when the frame 103 reaches its lowermost position, it will be wholly disengaged from the positioning element 27 and, consequently, also from the model S.

In these conditions, the container C, complete with the model S and the further quantity of sand it received at the substation 22, can be subjected to the vibration operation, which is performed, in a known manner, with the help of the generator 32a while the formations 31a keep the container C lifted off the trolley 50 used to transport it.

The said vibratory motion is applied to the body of the container while the model S is kept in a fixed position with respect to the container C by means of the various parts numbered 109 to 112. This ensures that the said vibratory motion, no matter how great its amplitude or intensity, will not be able either to displace the model S from its correct position or to cause a breakage of its gripping formation T, which in most cases will eventually define the channel through which the casting material will be poured into the container C.

On completion of the vibration operation, the lifting formations 31a will again lower the container C onto its trolley 50. At this point the jack 101 can be operated in the direction that will cause the structure 102 to become raised, while both the clamps 110 and the clamps 112 are opened, so that the positioning element 27 becomes disengaged from both the rim of the container C and from the grip formation T of the model S, which has to remain within the container C.

The frame 103 will therefore begin to rise and engage with the positioning element 27.

The presence of the centering formations 114a, 114b and their respective complementary formations ensures that the positioning element 27 will again become engaged with the frame 103 in an accurately defined position, so that the starting conditions indicated by means of the full lines in Figures 2 and 3 can eventually become exactly reconstituted.

When the structure 102 and the various elements it carries have eventually returned to their raised position, the container transport line can again be set in motion, so that the container C that has just been processed will be moved forward to substation 23 of Figure 1, while a new container will be moved from substation 21 to the device that constitutes substation 22.

While this is happening, the robot R has the time it needs to insert a new model S into the clamp of the positioning element 27 and the bottom outlet 20a of the silo 20 can be opened again to reconstitute the sand supply needed in the hopper 30 for the next filling.

In addition to the previously described advantages in connection with the operations of filling the sand into the container C and vibrating it, the solution according to the invention therefore has the further advantage of permitting the operations of loading the models S and filling the hopper 30 to be carried out while the containers are being moved, thus avoiding possible idle times.

As already mentioned in the introductory part of the present description, the substation 22 that has just been described in detail usually forms part of a plant or system that, in addition to the said substation 22 and the container transport system 50, includes also other stations and substations for carrying out the following technological operations in due succession:

- sand filling and vibration (other substations 21, 23 and 24 as already described)
- casting (one station)
- extraction of castings and sand (one station).

The last two of these stations are of a known type and have known characteristics and have not therefore been illustrated on the attached drawings.

As already mentioned, at the entry side of the system the clusters constituting the models S are loaded with the help of a buffer turntable that presents them to the robot R, which then picks them up from the turntable and automatically feeds them into the sub-station 22.

Given the different types of pieces (and therefore models and castings) that may have to be made, the following may vary:

- sand filling (speed at which the containers C are

filled, level to which the containers are filled at the various sub-stations 21-24);

- vibration (vibration frequency and/or duration);
- casting (quantity of metal to be cast, casting modalities);

- extraction of the castings (angle of inclination of the container when it is tipped to permit the castings to be picked up, usually by means of an anthropomorphic robot).

These variables and the possible changes associated with them can therefore be configured as a typical «recipe» for each casting.

The solution according to the invention is such that these functions can be completely automated. To this end, matters can be arranged in such way that the robot R, immediately after picking up a model S from the turntable, presents it in front of an identification station consisting, for example, of a television camera P and an appropriate model recognition module of a known type and possibly resident in the control unit K. The identification station recognizes the model S (among a set of possible models) and thereupon informs the system of the particular recipe needed for this model. This can be done by means of an appropriate type identification signal generated, for example, in the control unit K.

Once it has been inserted in the container C at the sand-filling station, the model S is - as it were - paired with the container (which is provided with a plate T, which could be - for example - of the magnetic or optical reading type, on which the casting data, recipe included, can be memorized). Prior to entry into each technological station, an electronic reader informs the station in question of the

Naturally, the realization details and the implementation forms can be widely varied with respect to what has here been described and illustrated without in any way altering the principle of the present invention or going beyond its scope as defined by the claims set out below.

WHAT IS CLAIMED IS:

1. A container-filling device for lost-foam casting systems, including in a single operational combination:

- supporting means for containers with associated vibration means to set the said containers into vibration;

- sand-feeding means capable of selectively feeding dosed quantities of sand into the said containers; and

- positioning means that can selectively be associated with the said containers to position foam models into the said containers; the said positioning means being capable of sustaining the said models both while the sand is being fed into the containers by the said feeding means and while the containers containing the said models are being vibrated by the said vibration means.

2. A device in accordance with Claim 1, including mobile equipment capable of performing a relative movement of lowering and raising with respect to the said containers and wherein the said sand-feeding means and the said positioning means are carried by the said mobile equipment.

3. A device in accordance with Claim 2, including also the following means, both capable of being activated while the said mobile equipment is in its raised position with respect to the said containers:

- loading means for selectively loading sand into the said feeding means, and

- means for handling the said models capable of selectively transferring the said models to the said positioning means.

4. A device in accordance with Claim 2, wherein the said

mobile equipment includes a bracket-like formation that sustains the said sand-feeding means and the said positioning means in what are, respectively, upper and lower positions.

5. A device in accordance with Claim 1, wherein the said sand-feeding means include a hopper structure.

6. A device in accordance with Claim 1, wherein the said positioning means include first gripping means capable of acting on the said models and second gripping means capable of acting on the said containers, so that, with the said first and second gripping means gripping, respectively, the models and the container, the said model and the said container will be substantially solidary to each other.

7. A device in accordance with Claim 6, including control means to bring the said first and second gripping means into their gripping position while the said vibration means are operating.

8. A device in accordance with Claim 6, wherein the said first and second gripping means consist, at least partly, of a clamp structure.

9. A device in accordance with Claim 6, wherein the said second gripping means have associated with them means for bringing them back into their open position.

10. A device in accordance with Claim 1, wherein the said positioning means have associated with them a respective moving structure from which the said positioning means can be selectively disengaged.

11. A device in accordance with Claim 10, wherein the said moving structure includes a frame that is solidary with the said mobile equipment and sustains the said positioning means, which rest on it; the arrangement being such that, when the said mobile equipment is in its lowered position relative to the said container, the said positioning means will become transferred to and rest on the said container, so that the said moving structure will be disengaged from both the said positioning means and the said container.

12. A device in accordance with Claim 11, wherein the said positioning means and the associated moving structure are provided with complementary centering formations capable of ensuring accurate positioning of the said positioning means and the said moving structure relative to the said container.

13. A device in accordance with Claim 12, wherein the said complementary formations include at least one pin-type element capable of engaging with a corresponding cavity.

14. A device in accordance with Claim 12, wherein the said complementary formations include a fork structure.

15. A device in accordance with Claim 1, further including:

- means for handling the said models capable of selectively transferring the said models to the said positioning means;

- shape recognition means associated with the said handling means and capable of recognizing, among a set of possible models, the particular type of models that, at that particular moment, is being carried by the handling means, generating a corresponding type identification signal.

ABSTRACT OF THE DISCLOSURE

The device, which can be used for filling containers in a lost-foam casting system, includes in a single operational combination:

- supporting means for containers with associated vibration means to set the said containers into vibration;


- sand-feeding means, such as a hopper, for feeding dosed quantities of sand into the said container; and


- positioning means that make it possible to locate foam models into containers and sustaining them both while the sand is being fed into the containers and while the containers are being vibrated, thus avoiding the risks of malpositioning and/or breakage. Preferably, both the sand-feeding hopper and model-positioning means on the same equipment capable of moving between a raised position in which the hopper may be loaded with the sand, while the foam models are being transferred to the positioning means, by means of a robot for example, and a lowered position, in which the models are inserted into the containers, after which the latter can be filled with sand.


(Figure 2)

00542015 022500

FIG. 1



[illegible]

[illegible]

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name: that I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural names are listed below) of the subject matter claimed and for which a patent is sought in the application entitled:

"Container-filling device for lost-foam casting systems"

which application is:

☒ the attached application
(for original application)

_____ application Serial No. _____
filed _____, and amended on _____

(for declaration not accompanying application)

that I have reviewed and understand the contents of the specification of the above-identified application, including the claims, as amended by any amendment referred to above; that I acknowledge my duty to disclose information of which I am aware which is material to the patentability of this application under 37 C.F.R. 1.56, that I hereby claim foreign priority benefits under Title 35, United States Code §119, §172 or §365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified on said list any foreign application for patent or inventor's certificate on this invention having a filing date before that of the application on which priority is claimed:

Application Number	Country	Filing Date	Priority Claimed (yes or no)
99830106.3	European Patent Office	February 26, 1999	YES

I hereby claim the benefit of Title 35, United States Code §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in a listed prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge my duty to disclose any information material to the patentability of this application under 37 C.F.R. 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.	Filing Date	Status (patented, pending, abandoned)
------------------------	-------------	--

I hereby appoint John H. Mion, Reg. No. 18,879; Donald E. Zinn, Reg. No. 19,046; Thomas J. Macpeak, Reg. No. 19,292; Robert J. Seas, Jr., Reg. No. 21,092; Darryl Mexic, Reg. No. 23,063; Robert V. Sloan, Reg. No. 22,775; Peter D. Olexy, Reg. No. 24,513; J. Frank Osha, Reg. No. 24,625; Waddell A. Biggart, Reg. No. 24,861; Robert G. McMorrow, Reg. No. 19,093; Louis Gubinsky, Reg. No. 24,835; Neil B. Siegel, Reg. No. 25,200; David J. Cushing, Reg. No. 28,703; John R. Inge, Reg. No. 26,916; Joseph J. Ruch, Jr., Reg. No. 26,577; Sheldon I. Landsman, Reg. No. 25,430; Richard C. Turner, Reg. No. 29,710; Howard L. Bernstein, Reg. No. 25,665; Alan J. Kasper, Reg. No. 25,426; Kenneth J. Burchfiel, Reg. No. 31,333; Gordon Kit, Reg. No. 30,764; Susan J. Mack, Reg. No. 30,951; Frank L. Bernstein, Reg. No. 31,484; Mark Boland, Reg. No. 32,197; William H. Mandir, Reg. No. 32,156; Scott M. Daniels, Reg. No. 32,562; Brian W. Hannon, Reg. No. 32,778 and Abraham J. Rosner, Reg. No. 33,276, my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and request that all correspondence about the application be addressed to **SUGHRUE, MION, ZINN, MACPEAK & SEAS**, 2100 Pennsylvania Avenue, N.W., Washington, D.C. 20037-3202.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Date December 22, 1999

First Inventor Alfredo DAL PAN
First Name Middle Initial Last Name

Residence TORINO (Italy)

Signature [Signature]

Post Office Address Via Induno 16, I-10137 TORINO (Italy)

Citizenship Italian